



ROLLER MILL 200 & 300


www.radeq.ca • info@radeq.ca


5490, Martineau Street, Saint-Hyacinthe (Québec) Canada J2R 1T8 Phone: (450) 796-2626 / Toll free: 1-888-796-2723 / Fax: (450) 796-1830

ROLLER MILL MODEL 200 & 300









END VIEW

45° PERPENDICULAR OUTLET

45° PARALLEL OUTLET

BAGING OUTLET

MODEL	DIMENSIONS												
	A	В	С	D	Е	F	G	Н	J	K	L	М	N MAX.
200	12 3/4	15 7/8	18 1/4	16 3/4	10 1/4	15 1/8	21 5/8	14 1/8	42	48 5/8	41 1/8	41	38 1/2
300	15 3/4	15 7/8	18 1/4	16 3/4	10 1/4	15 1/8	21 5/8	14 1/8	42	48 5/8	41 1/8	41	38 1/2

SPECIFICATIONS AND CAPACITY OF SINGLE ROLLER MILL

MODEL	ROLLER DIAMETER		CORRUGATION (TEETH/INCH)	DRY CORN	HIGH MOISTURE CORN	DRY SMALL GRAIN	HIGH MOISTURE SMALL GRAIN
200 6 1/2"		4 1/2"	5	4.3 T/H	3.7 T/H		
	6 1/2"		8.5 (INCLINED)	2.7 T/H	2.5 T/H	1.5 T/H	1.2 T/H
			10.5			1.2 T/H	1.0 T/H
300 6 1/2"		1/2" 7 1/2"	5	7.0 T/H	2.5 T/H		
	6 1/2"		8.5 (INCLINED)	4.5 T/H	4.2 T/H	2.5 T/H	2.0 T/H
			10.5			2.1 T/H	1.7 T/H

SUGGESTED MOTOR

MODEL	GRAIN	HP	RPM
200	CORN	2	1800
200	BARLEY	3	1800
300	CORN	3	1800
300	BARLEY	5	1800

Specifications are subject to change without notice.



* 57 ROCKWELL C TEMPERED STEEL ROLLER

* HEAVY STEEL ROBUST CONSTRUCTION

* EASY ACCESS MAGNET DRAWER

* EASY PRESSURE AND SPACING OF THE ROLLERS

* SAFETY MECANISM IN CASE OF FOREIGN OBJECT PASSING

* OTHERS ACCESSORIES AVAILABLE

MANUFACTURED BY: RAD Équipments inc. 5490, Martineau Street

St-Hyacinthe, Quebec, Canada J2R 1T8

Phone: (450) 796-2626 1-888-796-2723 Fax: (450) 796-1830 E-mail: info@radeq.ca Internet: www.radeq.ca **DISTRIBUTED BY**: